LINC SYSTEMS

IN-STOCK EQUIPMENT SALE

SML-150-S With Ramp

SAP# 01149SML15001225
SERIAL# 252864-1-0226

The Wulftec SML-150 Semi-Automatic Stretch Wrapper is a rugged, low-profile turntable wrapper designed for dependable pallet stabilization in demanding warehouse and manufacturing environments. Built as part of Wulftec's SMART™ Series, the SML-150 combines heavy-duty structural steel construction with advanced electrical controls to deliver long-term reliability, low maintenance, and consistent wrap quality. Its low-profile turntable base minimizes floor space and allows easy loading with forklifts, while the NO-THREAD® powered pre-stretch carriage maximizes film efficiency and ensures secure load containment from the pallet base upward. Featuring Allen-Bradley PLC controls, AC variable-frequency drives, and industry-leading warranties, the SML-150 is an excellent choice for operations seeking an affordable, yet industrial-grade stretch wrapping solution capable of handling loads up to 4,000 lbs.

Specifications:

- Production rate: Up to 55 loads per hour (application dependent)
- Turntable speed: Variable up to 16 RPM with automatic home position
- Maximum load weight: 4,000 lbs
- Maximum load size: Up to 50" × 50" × 80" (70" diagonal)
- Wrap height (standard): 80 inches
- Turntable diameter: 58 inches
- Film carriage: 20" NO-THREAD® Powered Pre-Stretch Carriage (30" optional)
- Pre-stretch ratio: 50%–300% standard (up to 400% depending on film type)
- Film tension: Electronically controlled with analog sensor
- Corner protection: Spring-loaded carriage gate for consistent wrap force
- Control system & Drives: Allen-Bradley MicroLogix / Micro800 PLC & Allen-Bradley AC Variable Frequency Drives
- Control cabinet: NEMA 4/12, dust-tight and waterproof, UL508A approved
- Features: Automatic load height photo-eye, Top and bottom wrap selectors, Manual carriage up/down control, Emergency stop and safety interlocks
- Power supply: 120V / 1-Phase / 60 Hz, 15A, No air
- Frame: Heavy-duty all-steel construction
- Carriage lift: Dual #50 chain-driven system, enclosed in tower for safety
- Safety features: Emergency stop, Safety-interlocked carriage gate, Enclosed electrical and drive components
- Overall dimensions: 118" L × 59" W × 86.5" H (based on 80" wrap height)
- Warranty: 5-year unlimited cycle warranty,10-year structural frame warranty, Lifetime pre-stretch roller blue compound warranty

$13,900.00

CALL 800.252.5894 NOW

for more information on our in stock equipment

INDUSTRIAL FASTENING EXPERTS | **PACKAGING PROBLEM SOLVERS** | **COMPLETE INDUSTRIAL SUPPLY**