

**PRE OWNED
EQUIPMENT SALE****Robopac Rotoplat 708**
SAP# 01167ROTOPLAT0522
SERIAL# 30228391

The Robopac Rotoplat 708 Semi-Automatic Stretch Wrapper is a premium turntable-style pallet wrapping solution engineered for maximum load stability, film efficiency, and operator control. Powered by Robopac's patented CUBE Technology, the Rotoplat 708 allows operators to precisely control pre-stretch, containment force, and film placement at multiple points on the load, reducing stretch film consumption by 30–55% while improving pallet integrity and reducing product damage.

Equipped with a 7-inch color touchscreen, powered pre-stretch carriage, and R-Connect remote monitoring, the Rotoplat 708 delivers consistent, repeatable wrap results across a wide range of pallet sizes and weights. Designed for demanding industrial environments, this semi-automatic wrapper is ideal for manufacturers and distribution centers seeking high-performance wrapping with minimal waste and maximum uptime.

Specifications:

- Production speed: Up to 40 loads per hour (application dependent)
- Turntable speed: 5–12 RPM (variable)
- Turntable drive motor & Carriage motor: 1 HP VAC & ½ HP VAC
- Maximum load weight and height: 4,400 lbs and 110" (standard)
- Maximum load size: Up to 40" × 48" pallet footprint
- Turntable diameter: 65 inches
- Construction: Heavy-duty diamond plate steel
- Film carriage: PVS (Powered Variable Stretch) carriage
- Pre-stretch range: 150%–400%, adjustable from control panel
- Containment force: Multi-level variable (adjustable up to 9 points per load)
- Film threading: Patented S-Wrap pattern for secure load reinforcement
- Corner compensation: Load-cell controlled to prevent crushed corners
- User interface: 7-inch color touchscreen with icon-based navigation
- Wrap programs: Store up to 6 custom load recipes
- Height detection: Automatic via photo-eye (light and dark loads)
- Connectivity: R-Connect remote machine monitoring (cloud-based, Industry 4.0 ready)
- Pressure-activated carriage safety stop & Emergency Stop
- Power: 115–120 VAC, single phase, 60 Hz, 12–20 amps (model dependent)

CALL 800.252.5894 NOW**for more information on our in stock equipment****INDUSTRIAL
FASTENING EXPERTS****PACKAGING
PROBLEM SOLVERS****COMPLETE
INDUSTRIAL SUPPLY**